




不等分割可變螺旋系列

Unequal Flute Spacing and Variable Helix Series



不等分割可變螺旋系列



Unequal Flute Spacing and Variable Helix Series

XVO 特長

1. 特殊的銑刀端面不等分割和不等螺旋角設計，於加工中抗震性更加良好，壽命佳。
2. XVO產品特殊的<4孔中心出水設計>，可應用於溝銑、側銑、插銑，排屑性良好，效率佳。
3. 應用於1D的高效率溝銑及側銑加工，排屑性及穩定性更佳。
4. 以特殊的中心出水設計來排屑及冷卻，並可用於一般鋼材(HRc45以下)及難切削材料，如不銹鋼、鈦合金、...等材料的插銑加工。
5. 可應用於高速擺線側銑加工，效率佳。
6. 系列產品之加工應用Vc值可達200 (m/min)以上。

Features of XVO

1. Unequal spacing of end teeth and variable helix design improve vibration resistance and provides longer tool life.
2. XVO is equipped with the special design " Four holes coolant through spindle system" .
It is ideal for slot milling, side milling, plunge milling and with high chip removal ability and milling efficiency.
3. 1D high efficiency slot milling and side milling.
High chip removal ability and superior stability.
4. The special coolant through spindle system is designed for chip removal and cooling. It can be used for plunge milling general steels(material below HRc45) and difficult-to-cut materials, such as stainless steel, titanium alloy and so on.
5. Ideal for high speed trochoidal side milling.
6. Vc can reach 200(m/min) and above.

4T

XVO

抗震高效能立銑刀 (內冷孔)

End Mills

Internal Coolant Hole



型號 Type No.	D1 直徑 Diameter	L1 刃長 Flute Length	L3 全長 O. A. L.	D2 柄徑 Shank Dia
XVO0604	6.0	15	50	6
XVO0804	8.0	20	60	8
XVO1004	10.0	22	75	10
XVO1204	12.0	26	75	12

unit: mm



德信發企業有限公司

DHF Precision Tool Co., Ltd.

營運總部 Head Office

台灣台中市西屯區市政北二路282號28F-5

28F-5., No. 282, Shizheng N. 2nd Rd., Xitun Dist., Taichung City 40756, Taiwan

TEL : 886-4-22587585 FAX : 886-4-22585985

<http://www.endmill.com.tw>

E-mail : dhf@endmill.com.tw

分公司 Branch

Italy / Pordenone

DHF Italia Srl <http://www.dhfitalia.it>

Turkey / Istanbul

DHF Sert Kesici Takimlar

Poland / Katowice

DHF Polska Sp z o.o.

China / GuangDong

東莞市虎門鎮索菲特東方時代廣場

TEL / 0769-85115970 FAX / 0769-85240930

經銷商 Distributor

Spain / Sondika-Bizkaia

JANA-TOOL, S.L.

Distributor



2019.01. 2000